

Troy Acoustics Shooting Range Acoustics order form 2015- Rev 1

Part #	Troy System Description	Typically used on	Your total square footage requirement including waste	to be calculated by TAC (Plus Shipping & Handling)
TBWF-1-B-Z	Troy System 1" Board (2' x 7' 10 1/2" per board) and 2" Wool with 10 - 2" Fasteners EXCLUDES metal furring/z-channel and anchors	Baffles, Safety Ceiling		
TBWF-2-B-Z	Troy System 2" Board (2' x 7' 10 1/2" per board) and 2" Wool with 10 - 3" Fasteners INCLUDES metal furring/z-channel and anchors	Sidewalls		
TBWF-2-6-B	Troy System 2" Board (2' x 7' 10 1/2" per board) and 6" Wool with 10 - 3" Fasteners (for use on wood or metal furring/z-channel – please specify supplied by others)	Sidewalls for isolation		
TBWF-6-B	Troy System 1" Board (2' x 7' 10 1/2" per board) and 6" Wool (excludes 2' x 2' commercial grid supported 4' in 2 directions)	Sub-ceiling for absorption and isolation		
TBW-2-tile	Troy System acoustic tile (2' x 2' x 1") and 6" Troy Wool (excludes 2' x 2' commercial grid supported 4' in 2 directions)	Drop ceiling/isolation ceiling		
Shipping	Delivery of all materials to address below.	Delivery		

I/We _____ (hereinafter referred to as Customer) would like to order the above material. Please supply pricing for shipping & handling to the address below. It is understood that Troy Acoustics will not provide cut or partial Troy Board materials, and that price will include partial boards round up to full boards.

Customer/Company Name:

Customer/Company Address:

Phone:

E-mail:

Do you have a loading dock?

Method of payment: Credit Card _____ Certified Check _____
Wire Transfer _____ Other (please specify) _____

Troy Acoustics will provide pricing (including shipping (most economical truck)) and instructions regarding payment upon receipt of this order form. The \$ 7.75 per sq. ft. pricing excludes sales tax (if applicable) & shipping. This is a materials only procurement and does not constitute any guaranteed results. Design services, including site specific design, shop drawings; pre and post testing are fee based services and are available upon request. Customer understands accepts responsibility for the procurement of furring strips, z-channel, j-channel, spray adhesive and paint. Although not required, it is recommended that the Troy System is painted with 3 coats of acrylic latex paint with an airless sprayer. Customer has been advised that the Troy System materials for a ceiling application can be installed in a heavy duty drop ceiling type grid supported 4' o.c in two directions. The Troy Board material can be saw-cut to fit.

Signature: _____

Date: _____